



19932 West 157th Street
Olathe, Kansas 66062
(800) 669-6288
(913) 829-6787
Fax (913) 829-6821

Prentice TS-33 Material Handling Crane

4 Story Reach

Top Seat

Crane Rating – 150,922 Ft. Lbs.

Maximum Capacity – 4,000 lbs. At 46' (Vertical)

Maximum Horizontal Reach – 33'

Capacity at Maximum Horizontal Reach – 3,400 lbs.

Rotation – 360° Continuous

Outriggers – Hydraulic Flop Down

Outrigger Spread – 15' at Grade

Oil Tank Capacity – 47 Gallons

Pump Type – Low Pressure, High Volume, Gear Type - Double Circuit

Pump Capacity – 21X24 G.P.M.

Crane Weight – 9,180 lbs. (Approximate)

Mounting Space Required – 40"

Palfinger/Kinshofer 63" Wallboard Fork

54" throat

6,000 lb. capacity

25' Heavy Duty Steel Flatbed with Headboard

3/16" Treadplate Flooring

Recessed ICC Clearance Lights and Tail Light Guards

(6) Ratchets with 4" Straps on Sliding Track

Combination boom & fork support with winch & strap to tie down fork

PTO/Pump Combination

Air Shift PTO

Electronic Speed Control

18"X18"X36" Underbody Toolbox

D.O.T. Safety Kit

Back-Up Alarm

Complete Installation and Testing

All Steel Fabrication Painted Black Enamel